



WSEFV系列

三相超高效TENV结构NEMA电机

型号	功率	转速 50Hz	机座	尺寸	防护	效率	满载电流	功率因素	效率
WSEFV5612	1/4	3460	56	230/460	TENV	1.15	0.88/0.44	0.7805	65.6
WSEFV5614		1760	56	230/460	TENV	1.15	1.10/0.55	0.5924	69.5
WSEFV5622	1/3	3460	56	230/460	TENV	1.15	1.10/0.55	0.8035	69.5
WSEFV5624		1765	56	230/460	TENV	1.15	1.38/0.69	0.5967	73.4
WSEFV5632	1/2	3460	56	230/460	TENV	1.15	1.50/0.75	0.8219	73.4
WSEFV5634		1765	56	230/460	TENV	1.15	1.92/0.96	0.6260	78.2
WSEFV5642	3/4	3450	56	230/460	TENV	1.15	2.06/1.03	0.8542	76.8
WSEFV5644		1760	56	230/460	TENV	1.15	2.46/1.23	0.6819	81.1
WSEFV5652	1	3480	56	230/460	TENV	1.15	2.66/1.33	0.8711	77.0
WSEFV5654		1760	56	230/460	TENV	1.15	3.10/1.55	0.7122	83.5
WSEFV5664	1.5	1755	56	230/460	TENV	1.15	4.28/2.14	0.7527	86.5
WSEFV5674	2	1750	56	230/460	TENV	1.15	5.48/2.74	0.7805	86.5
WSEFV14312	3/4	3450	56	230/460	TENV	1.15	2.06/1.03	0.8542	76.8
WSEFV14314		1760	56	230/460	TENV	1.15	2.46/1.23	0.6819	81.1
WSEFV14322	1	3480	56	230/460	TENV	1.15	2.66/1.33	0.8711	77.0
WSEFV14324		1760	56	230/460	TENV	1.15	3.10/1.55	0.7122	83.5
WSEFV14534	1.5	1755	56	230/460	TENV	1.15	4.28/2.14	0.7527	86.5
WSEFV14544	2	1750	56	230/460	TENV	1.15	5.48/2.74	0.7805	86.5

